


TECHNICAL SPECIFICATIONS:
 MIN. PRESSURE: 80 PSI
 MAX. PRESSURE: 175 PSI
 MAX. INLET FLOW: 17 CFM
 MAX. INLET AIR TEMPERATURE: 150°F
 POWER SUPPLY: 120 VAC

01	Lighter Piston Spring	03/25/22	CDG
000	Initial Release	06/16/20	CDG
NO.	REVISION	DATE	APPR



PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SUBURBAN MANUFACTURING INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SUBURBAN MANUFACTURING INC IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:
 DIMENSIONS ARE IN INCHES
 TOLERANCES:
 ANGULAR: MACH±1°
 BEND ±2°
 FRACTIONAL: ± 1/16
 ONE PLACE DECIMAL ± 0.050
 TWO PLACE DECIMAL ± 0.010
 THREE PLACE DECIMAL ± 0.005
 FOUR PLACE DECIMAL ± 0.0005
 INTERPRET GEOMETRIC TOLERANCING PER: ANSI Y14.5 - 2009
 MATERIAL
 FINISH 125
 DO NOT SCALE DRAWING

	INITIALS	DATE
DESIGNED	CDG	08/05/19
DRAWN	JSM	03/17/22
MFG ENG APPR.	NAB	03/25/22
ENG APPR.	CDG	03/25/22

COMMENTS:



TITLE: 5 HP Dual Tower Dryer

DWG. NO. 21999-1105	REV 01
SIZE: B SCALE: 1:5 WEIGHT:	SHEET 1 OF 1